

Date of issue: 01-07-08

Revision no. 4

Datasheet:

M93 feed grade

- M93**
- is a ground powder of caustic calcined magnesite (magnesium oxide)
 - is produced by mining and calcination of natural raw magnesite
 - is used in animal feed for **mineral mixes, premixes and compound feed**
 - is conforming with EU regulations for heavy metals and dioxine

Chemical Analysis:

		typical		min./max.	
MgO	(Magnesium Oxide)	93,0	%	min. 90,0	%
Mg	(Magnesium)	56,0	%	min. 54,0	%
Fe ₂ O ₃	(Iron Oxide)	0,6	%	max. 0,8	%
LOI	(Loss of ignition)	2,5	%	max. 6,0	%

Heavy metals:

	typical	
Pb (Lead)	< 5	ppm
As (Arsenic)	1	ppm
Cd (Cadmium)	< 1	ppm
Hg (Mercury)	< 0,1	ppm
F (Fluorine)	400	ppm

Physical Parameters:

Colour: beige to light brown

Particle size: minimum 95 % < 125 micron

Bulk density (EN 459-2): ca. 850 g / l

Please note:

- All information is based on data available at the date of issue. This datasheet is an uncontrolled copy which will not be updated automatically.
- The chemical and physical data refer to analyses of incoming raw material. Other specifications for minimum and maximum values can be given on request. Please contact our sales department.
- No guarantee is implied or expressed regarding the use of the product, since the conditions for use are beyond our control.